TC 系列二联件－金属杯子型





- TC2010–02M
- TC2010–02DM
- TC3010–03M
- TC3010–03DM
- TC4010–04M
- TC4010–04DM


Character

Metal cup is of metal material die–casting forming. It's reliable , durable ability and anti–explosion. Besides, it has long use life and safe use.

Ordering Code

TC	2010	—	02	M
Series	Type 1010 2010 3010 4010 5010		Pipe size 01 : G1/8 02 : G1/4 03 : G3/8 04 : G1/2 06 : G3/4 10 : G1	M:Metal cups D:Automatic drain type

Graphics Sign




Technical Parameter


Specification		TC2010–02M/02DM/01M/01DM	TC3010–03M/03DM/02M/02DM	TC4010–04M/04DM/03M/03DM	TC4010–06M/06DM	TC5010–10M/10DM/06M/06DM
Applicable Medium		Air				
Rating Flow(L/min)		500	1700	3000	3000	4000
Filtration		5 μm ～ 40 μm				
Applicable Pressure Range		0.05 ～ 1MPa				
Medium Temperature		0 ～ 60℃				
Recommended Lubricating Oil		ISOVG32 or Equivalent				
Type of Valve		Relief Type				
Gauge Port Size		G1/8		G1/4		
Components	Filter Regulator	TW2000–02M/02DM/01M/01DM	TW3000–03M/03DM/02M/02DM	TW4000–04M/04DM/03M/03DM	TW000–06M/06DM	TW5000–10M/10DM/06M/06DM
	Air Lubricator	TL2000–02M/02DM/01M/01DM	TL3000–03M/03DM/02M/02DM	TL4000–04M/04DM/03M/03DM	TL4000–06M/06DM	TL5000–10M/10DM/06M/06DM

Figure Dimension

- TC2010–02M/01M



- TC3010–03M/02M　TC4010–04M/03M
  TC4010–06M　TC5010–10M/06M



Type	A	B	C	D	E	F	G	H	K	J	M	Automatic drain type
												B
TC2010–02M/02DM/01M/01DM	90	205	72.5	40	30	53	G1/4	48	9	5.5	6	205
TC3010–03M/03DM/02M/02DM	117	226	89	53	41	56	G3/8	70	13	7	7	241
TC4010–04M/04DM/03M/03DM	154	277	114	70	50	62	G1/2	80	11	9	7	292
TC4010–06M/06DM	164	277	114	70	54	62	G3/4	80	13	10	7	292
TC5010–10M/10DM/06M/06DM	195	355	118	90	74.5	72	G1	103	17	13	10	370